



NEW STREETLIGHT FLEX LUMINAIRES



STREETLIGHT FLEX

The new STREETLIGHT FLEX combine robust design with outstanding quality for long-lasting performance for streetlight and parking applications. Thanks to tool-free opening of the housing and push button terminals they are very easy to connect to the mains. At 0° tilt, no light is emitted to the sky (ULOR 0 %). The flexible spigot allows for post-top and side-entry mounting and $\pm 15^\circ$ tilt adjustment is possible without opening the housing.

Further benefits are high uniformity, three light colors, automatic mains disconnection when opening the housing and last but not least, a 5-year guarantee.

TECHNICAL FEATURES

- Efficacy: up to 155 lm/W
- Light color: 2700K, 3000K, 4000K all CRI >70
- Housing color: White aluminum (similar RAL 9006)
- 2 beam angles for road lighting and parking
- Lifespan: up to 100,000 hours (L90/B10 @ 25°C)
- Operating temperature: -40 to $+50^\circ\text{C}$
- Guarantee: 5 years
- Side-entry or post-top installation (60mm pole diameter as standard, 42/76mm via accessories)
- 10 kV (L/N-GND), 6kV (L/N) surge protection





Small



Medium



Large

Beam angle 25° SL FLEX LA P 158W 740
RV25ST WALBeam angle 35° SL FLEX LA P 158W 740
RW35ST WAL

Detailed product
and order data
available soon.